Topclear

TECHNICAL DATASHEET

PRODUCT INFORMATION	
Category	Cleaner to remove shading coatings
Description	Topclear is the cleaner for effectively removing Sudlac removable shading and diffusion coatings. With Topclear growers have full control when they remove the coating from their greenhouse. To remove Optifuse and Optifuse IR, a special version of Topclear is needed: Topclear Fuse
Properties	• Easy to apply • Dilute with clean water • Apply in dry weather • Applicable to all types of greenhouses
Recommended use	For the removal of Sudlac shading coatings
Recommended surface	Suitable for glass, acrylate, polycarbonate and plastic film
Identified users	Industrial – for professional use only

TECHNICAL SPECIFICATIONS	
Physical state	Liquid
Colour	Colourless
Odour	Characteristic
pH	13
Flammability (solid, gas)	Non flammable
Explosive properties	None
Density	1.1 g/cm³
Viscosity	1600 mPa·s Brookfield, 5 rpm, 20°C
Transport regulation (ADR, RID, IMDG, IATA, IDN)	Yes, class (ADR): 8, packing group: III

STORAGE CONDITIONS	
Packaging	20 L can 1 pallet contains 48 cans
Shelf life	Unopened containers have a shelf life of 3 years. Keep only in the original container in a cool, well-ventilated place. Products should be protected against frost (below 0°C) and overheating (above 35°C).

This technical datasheet is based on many years of experience. Lumiforte can not be held liable for any damages resulting from the use of this product or any damages beyond her control. The customer should check, using the means normally available to him, whether the products supplied are suitable for the planned application. If in doubt, consult our technical specialists via welcome@lumiforte.com.

Sudlac is a brand of Lumiforte®

Geerstraat 8, 5111 PS Baarle-Nassau
The Netherlands
T: +31 (0)13 50 75 399 I CofC 18029088

1 Rue Gaston Monmousseau, 38130 Echirolles
France
T: +33 (0)4 76 23 20 54 I CofC 062 500 954

Topclear

TECHNICAL DATASHEET

INSTRUCTIONS FOR USE	
Surface preparation	Shake cans well before use. Check whether the waterways and surroundings are suitable for the inflow of Topclear. Preferably close the inlet of the irrigation basin from the start of the application until the shading material is removed. Note: Standard greenhouse cover materials will not be damaged by Topclear. For specially treated greenhouse cover materials (diffuse glass, AR coatings), please contact your supplier.
Weather conditions	• Spray the solution evenly onto a dry greenhouse surface in dry weather and at a minimum temperature of 5°C • Wind speed of less than 2 m/s (7 km/h) • Relative humidity (RH) < 90 % • Do not apply Topclear on a wet surface or during rain because it needs at least 20 minutes to react with the coating
Equipment	Application should be done by spraying the liquid on the surface: • By spraying machine • By hand with a spray gun • By helicopter
Personal protection	Avoid contact with skin and eyes and wear a safety mask, protective gloves and protective clothing.
Dilution	Spray at least 240 L Topclear diluted with 1,260 or 1,760 liter water per hectare depending on the application method. Stir continuously.
Application	Apply Topclear evenly to a dry greenhouse surface and allow it to soak in for at least 20 minutes before brushing. Or apply Topclear when a considerable amount of rain is expected within one week. The rain will wash off the coating. Make sure that the entire coating is moistened. Sections that are not moistened will not be re-moved. Note: Use of roof-sprinklers for cooling can cause removal problems. Do not use rooftop sprinklers for rinsing purposes. Do not use any other cleaning agents to remove Sudlac coatings.

EFFECT ON CROPS AND ENVIRONMENT	
Environmental precautions	Always dilute products with water in the right amount before use and rinse with a large amount of water. Dispose in a safe manner in accordance with local/national regulations. Avoid visual discoloration (temporary and harmless) of the water by: • Dispose in a wide river with sufficient capacity and enough flow • A discharge point above the waterline can cause foaming, drain the pipe under the waterline If the cleaning water is collected and re-used: facility needs separate compartments because the remains of the coating and cleaner need time to settle down. Check the usability of the irrigation water in the basin after cleaning.

This technical datasheet is based on many years of experience. Lumiforte can not be held liable for any damages resulting from the use of this product or any damages beyond her control. The customer should check, using the means normally available to him, whether the products supplied are suitable for the planned application. If in doubt, consult our technical specialists via welcome@lumiforte.com.

Sudlac is a brand of Lumiforte®

Geerstraat 8, 5111 PS Baarle-Nassau
The Netherlands
T: +31 (0)13 50 75 399 I CofC 18029088

1 Rue Gaston Monmousseau, 38130 Echirolles
France
T: +33 (0)4 76 23 20 54 I CofC 062 500 954